

STAR LED Flood Asym



150 lm/W

Flutlicht mit asymmetrischen Abstrahlwinkel

Floodlight with asymmetric beam angle

EIGENSCHAFTEN

- Ersatz für Halogenstrahler
- Verstellbarer Stahlbügel für Wand- und Deckenmontage
- 6kV Überspannungsschutz
- Nichia LED-Chip
- Meanwell-Vorschaltgerät
- Asymmetrischer Abstrahlwinkel
- Effizienz: 150 lm/W
- Bis zu 36.000lm
- 5,000K
- IK08 und IP66
- 70.000 Stunden Lebensdauer
- -30°C - +45°C
- CRI>70
- 5 Jahre Garantie

ANWENDUNGSBEREICHE

- For the lighting of billboards, facade illumination, parking lots, sports facilities indoors and outdoors

FEATURES

- Replacement for halogen floodlights
- Adjustable steel bracket for wall and ceiling mounting
- 6kV surge protection
- Nichia LED chip
- Meanwell driver
- Asymmetric beam angle
- Efficiency: 150 lm/W
- Up to 36,000lm
- 5,000K
- IK08 and IP66
- 70,000hrs lifetime
- -30°C - +45°C
- CRI>70
- 5 year warranty

AREAS OF APPLICATION

- For the lighting of billboards, facade illumination, parking lots, sports facilities indoors and outdoors



EiKO 



EiKO-Europe GmbH
Mittelwegring 20
76751 Jockgrim
Germany

© 2024 Eiko-Europe GmbH
www.eiko-europe.de
+49 (0) 7271 7607 0
info@eiko-europe.de